

## Colliers double fil W1, W4

Le collier double fil permet de serrer des tuyaux annelés et polyéthylène dans le domaine de la maintenance, de l'irrigation, de la ventilation, etc..



ZFT

ZFP

Collier dit en tirant

Ø mm min-max	W1
9,5-12	ZFT12
10,5-13	ZFT13
11,5-14	ZFT14
12,5-15	ZFT15
13-16	ZFT16
13,5-17	ZFT17
15-18	ZFT18
15,5-19	ZFT19
17-20	ZFT20
17,5-21	ZFT21
18,5-22	ZFT22
19-23	ZFT23
21,5-25	ZFT25
23,5-27	ZFT27
27-31	ZFT31
30,5-35	ZFT35
33-37	ZFT37
35,5-40	ZFT40
38,5-43	ZFT43

Ø mm min-max	W1
43,5-49	ZFT49
46,5-53	ZFT53
50,5-56	ZFT56
56,5-64	ZFT64
64-72	ZFT72
72,5-80	ZFT80
80-88	ZFT88
88-96	ZFT96
95-104	ZFT104
103-112	ZFT112
111-120	ZFT120
117-128	ZFT128
125-140	ZFT140
135-150	ZFT150
145-160	ZFT160
155-170	ZFT170
165-180	ZFT180
175-190	ZFT190

Collier dit en poussant

Ø mm min-max	W1	W4
13-16	ZFP16	IFP16
15-18	ZFP18	IFP18
17-21	ZFP21	IFP21
20-23	ZFP23	IFP23
22-25	ZFP25	IFP25
24-27	ZFP27	IFP27
27-31	ZFP31	IFP31
31-35	ZFP35	IFP35
33-37	ZFP37	IFP37
35-40	ZFP40	IFP40
38-43	ZFP43	IFP43
43-48	ZFP48	IFP48
45-50	ZFP50	IFP50
49-55	ZFP55	IFP55
54-60	ZFP60	IFP60
59-65	ZFP65	IFP65
64-70	ZFP70	IFP70
69-75	ZFP75	IFP75
74-80	ZFP80	IFP80