

BREEZE LINER



- ① **High-strength Quadra-Lock housing construction**
- ② **7,9mm hexagonal slotted screw**
- ③ **Lined band protects hose from damage**

Extension clamp

An integral extension of the band as an inner liner protects soft-surface hose (silicone and others) from damage caused by extrusion or shearing through the band slots. Liner clamps afford

maximum protection to soft hoses while providing a true concentric seal.

Advantages at a glance

- Inner liner which protects all types of hoses from damage
- SAE Standard J1508 Type F

Materials



* Classified by corrosion resistance. Band material S40/Screw material S10. According to DIN norms it would be comparable to W2

** Classified by corrosion resistance. Band material S40/Screw material S30.

Typical applications

- Commercial vehicle
- Passenger vehicle
- Industrial
- Infrastructure

Specifications

BREEZE LINER				
Width (B mm)	Clamping ranges (D mm)	Clamping ranges (D in.)	S10 Product No. Carbon screw	S30 Product No. 410 Stainless screw
12,7	11-20	7/16-25/32	0361 0200 016	0361 0122 016
	13-23	1/2-29/32	0361 0200 018	0361 0122 018
	14-27	9/16-11/16	0361 0200 021	0361 0122 021
	17-32	11/16-11/4	0361 0200 025	0361 0122 025
	21-38	13/16-11/2	0361 0200 030	0361 0122 030
	21-44	13/16-1 3/4	0361 0200 033	0361 0122 033
	27-51	1/16-2	0361 0200 039	0361 0122 039
	33-57	15/16-2 1/4	0361 0200 045	0361 0122 045
	40-64	19/16-2 1/2	0361 0200 052	0361 0122 052
	46-70	1 13/16-2 3/4	0361 0200 058	0361 0122 058
	52-76	2 1/16-3	0361 0200 064	0361 0122 064
	59-83	2 5/16-3 1/4	0361 0200 071	0361 0122 071
	65-89	2 9/16-3 1/2	0361 0200 077	0361 0122 077
	71-95	2 13/16-3 3/4	0361 0200 083	0361 0122 083
	78-102	3 1/16-4	0361 0200 090	0361 0122 090
	84-108	3 5/16-4 1/4	0361 0200 096	0361 0122 096
	91-114	3 9/16-4 1/2	0361 0200 103	0361 0122 103
	105-127	4 1/8-5	0361 0200 116	0361 0122 116
	117-140	4 5/8-5 1/2	0361 0200 129	0361 0122 129

Dimensions

